





Model	E30
Operating weight	2650
Bucket capacity	0. 08
Engine model	YANMAR 3TNV80F
Rated power (kw/r/min)	14. 6/2500
Max.flow (L/min)	67. 2
Working pressure (Mpa)	22
Fuel tank capacity (L)	35
Hydraulic oil tank capacity (L)	28
Travel speed (km/h)	2. 0/3. 2
Swing speed (r/min)	11. 5
Max. climbing degree (%)	58
Arm digging force	14. 2
Bucket digging force (KN)	20
Average grounding pressure (Kpa)	30. 5
Largest traction(KN)	
A-Overall length (mm)	4159. 0
B-Overall width (mm)	1550
C-Overall height (to top of boom)(mm)	1636. 0
D-Overall height (to top of cab)(mm)	2560
E-Counterweight ground clearance(mm)	535. 0
F-Min. ground clearance (mm)	320
G-Tail swing radius (mm)	775. 0
H-Track ground length(mm)	1600
J-Track length (mm)	2040. 0
K-Track gauge (mm)	1250
L-Track width (mm)	1550. 0
M-Track shoe width (mm)	250
N-Turntable width (mm)	1375. 0
O-Max. digging height (mm)	4132
P-Max. dumping height (mm)	2742. 0



Q-Max. digging height (mm)	2485
R-Max. vertical wall digging depth (mm)	2240. 0
T-Max. digging reach (mm)	4610
U-Max. digging reach at ground level (mm)	4494. 0
V-Min. swing radius (mm)	2096
X-Distance between center of rotation and tail length (mm)	775. 0
Y-Track shoe thickness (mm)	5. 5
Z-Height of counterweight (mm)	300. 0
A1-Ground length (in transportation)(mm)	2908
Arm length (mm)	1150. 0
Boom length (mm)	2015
Deflection angle left°/right°	47/74
Maximum dozing height/depth (mm)	362/383