

# K1000ET Loader



## Specifications

	Model	K1000ET	
Specification	Rated load (kg)	900	
	Bucket Capacity(m <sup>3</sup> )	0.26	
	Max.Lifiting Height of main boom(mm)	3340	
	Max.Dumping height of main boom(mm)	2066	
	Max.Dumping distance of main boom(mm)	547	
	Max.Loding capacity of main boom(kg)	900	
	Max.Lifting Height of small boom(mm)	3886	
	Max.Dumping height of small boom(mm)	2658	
	Max.Dumping distance of small boom(mm)	1036	
	Max.Loding capacity of small boom (mm)	600	
	Max.Speed (km/h)	Forward 1	12
		Reverse 1	12
	Max.digging depth(mm)	65	
	Max.gradeability	25°	
	Max.steering angle	35°	
Dimession	Full length (bucket on ground position) (mm)	3960*1320*2390	
	Wheel base (mm)	1100	
	Tread (mm)	890	
	Min.ground clearance (mm)	220	
	Net weight(kg)	2460	
Battery	Battery Model No.	3-EVF-200A	
	rated capacity (3hr)	200Ah	
	No.of battery groups	12	
	Rated Voltage	72	
	Working hours (h)	4h	
Transmission System	Hydraulic System	Motor No.	YQP5.72AF.48P
		Voltage	72V
		Power	5000W
	Tyres	Displacement ( ml/r)	14
		Type	29*12.50-15
		working pressure ( mpa)	0.3
Qty	4		
Steering System	Type of Steering Hydraulic System	Full Hydraulic Steering System	
	System Pressure ( mpa)	16	
	Type of Steering Pump	External Gear Pump	
	Steering Cylinder Bore (mm)	Ø65	
	Qty (pc)	1	
Braking System	Service Brake	Drum Brake	
	Brake Drum (mm)	240	
	Parking Brake	Drum Brake	
Oil Capacity	Hydraulic Oil Tank (L)	40	
	Brake Fluid (L)	0.8	