

K1600 LOADER SPEC SHEET



Features:



Luxury Cabin



Flip-up Engine Hood



Adjustable Steering Wheel



Compact/ Beautiful design



Orderly Hydraulic Pipe



Hydraulic Quick Hitch

Specifications:

Performance	Rated loading (kg)	1600
	Overall weight (kg)	3800
	Rated bucket capacity (m ³)	0.65
	Maximum tractive force (kN)	33
	Maximum breakout force (kN)	28
	Maximum grade ability(°)	20
	Maximum dump height(mm)	2394
	Maximum dump reach(mm)	1034
	Overall dimension (L×W×H)(mm)	5095*1850*2557mm
	Minimum turning radius (outside of wheels)(mm)	5210
	Maximum steering angle	31°
	Oscillation angle	8°
Transmission system	Torque converter	265
	Gearbox mode	Power shift normally engaged straight gear
	Gear shift	Electric, 2forward shift 2 reverse shift
	Maximum speed	19km/h
Drive axles	Main reducing mode	Bevel gear grade I reduction
	Wheel base (mm)	2282
	Wheel tread(mm)	1400
	Ground clearance(mm)	400
Hydraulic system	System working pressure (Mpa)	18
	Boom lifting time (s)	4
	Total time (s)	7
	Fuel tank capacity (L)	75
	Function of leveling automatically	yes
Brake system	Service brake	Air-assist hydraulic, disc brake
	Parking brake	Manual disc brake
Tyre	Type specification	23.5/70-16
	Front tyre pressure (kPa)	320
	Rear tyre pressure (kPa)	320