

# KME10 MINI EXCAVATOR SPEC SHEET



## Features:

<p><b>Reinforced Fuel Tank</b></p>	<p><b>Hydraulic Oil Radiator</b></p>	<p><b>Hydraulic Safety Lock</b></p>
<p><b>Fully Opening Engine Hood</b></p>	<p><b>Thickened Counterweight</b></p>	<p><b>Wide Foot Space</b></p>
<p><b>Oil-Water Separator</b></p>	<p><b>Strong bulldozer</b></p>	<p><b>New valve box</b></p>

## Specifications:

Type of cab		Canopy	
Bucket capacity		m3	0.023
Bucket width, std.		mm	400
Machine weight		kg	960
Dimensions	Overall length	mm	2876
	Overall height	mm	2220
	Overall width	mm	880
	Ground clearance	mm	132
Engine	Brand	KOOP	
	Model	KD192F-1	
	Displacement	L	0.499
	Output	kW/rpm	7.0/3000
Working ranges	Max Digging height	mm	2600
	Max Dumping height	mm	1830
	Max digging depth	mm	1715
	Max. Digging radius	mm	3065
	Min .swing radius	mm	1483
	Max digging force (Arm)	kN	4.6
	Max digging force (Bucket)	kN	7.2
Track	Type	Rubber track	
	Rubber shoe width	mm	180
Undercarriage	Track length	mm	1233
	Traveling speed	km/h	2
	Gradeability	deg	58/30
Swing speed		rpm	13
Ground pressure		kpa	20
Dozer size	Width	mm	840
	Height	mm	240
	Lifting capacity (Height/Depth)	mm	150/200
Hydraulic pumps	Type	1 Gear pump	
	Flow rate	L/min	18
	Hydraulic pressure	Mpa	16
Swing motor		Cycloidr motor	
Travel motor		Cycloidr motor	
Fuel tank capacity		L	7
Hydraulic oil tank capacity		L	14.5