

# KMZ40 EXCAVATOR SPEC SHEET



## Features:

<p><b>Zero Tail</b></p>	<p><b>Hydraulic Control</b></p>	<p><b>Full Opened Engine Hood</b></p>
<p><b>Kubota 1703 Euro 5 engine</b></p>	<p><b>Openable Windshield</b></p>	<p><b>Digital Dashboard</b></p>
<p><b>Bulldozer</b></p>	<p><b>Pedal and AC</b></p>	<p><b>Eddie Walking Motor</b></p>

## Specifications:

Type of cab		Cabin	
Bucket capacity		m3	0.12
Bucket width		mm	570
Machine weight		kg	3810
Dimensions	Overall length	mm	4915
	Overall height	mm	2525
	Overall width	mm	1720
	Ground clearance	mm	295
Engine	Brand	Kubota	
	Model	D1703	
	Output	KW	18.5
Working ranges	Max digging height	mm	4800
	Max dumping height	mm	3406
	Max digging depth	mm	3208
	Max. digging radius	mm	5480
	Min .swing radius	mm	2530
	Deflection angle(Left/Right)	°	55/65
	Swing radius at tail	mm	860
	Swing radius at front	mm	2530
	Max digging force (Arm)	kN	18.2
	Max digging force (Bucket )	kN	30.4
Track	Type	Rubber track	
	Track grounding length	mm	1670
	Track length	mm	2154
	Track gauge	mm	1420
Dozer size	Height	mm	350
	Maximum lifting height	mm	365
	Maximum cutting depth	mm	385
Traveling speed		km/h	2.4/4.4
Gradeability		deg	58%/30°
Swing speed		r/min	12
Ground pressure		kpa	32
Hydraulic pressure		Mpa	22.5
Fuel tank capacity		L	40
Hydraulic oil tank capacity		L	44