

K2500T TELESCOPIC LOADER SPEC SHEET



Features:



Luxury Cabin



Flip-up Engine Hood



Adjustable Steering Wheel



Compact/ Beautiful design



Short Hydraulic Pipe



Customizable Quick Hitch

Performance	Rated loading (kg)	2500
	Overall weight (kg)	5100
	Rated bucket capacity (m ³)	0.67
	Maximum tractive force (kN)	35
	Maximum breakout force (kN)	25
	Maximum grade ability (°)	25
	Maximum lifting height of small boom (mm)	5413
	Maximum dump height of main boom (mm)	2768
	Maximum dump height of small boom (mm)	3766
	Maximum dump reach (mm)	1012
	Overall dimension (L×W×H) (mm)	5631*1870*2736
	Minimum turning radius (outside of wheels) (mm)	5068
	Maximum steering angle	40°
	Oscillation angle	5°
Transmission system	Torque converter	265
	Gearbox mode	Power shift normally engaged straight gear
	Gear shift	Mechanical, 2forward shift 2 reverse shift
	Maximum speed	21km/h
Drive axles	Main reducing mode	Bevel gear grade I reduction
	Wheel base (mm)	2568
	Wheel tread(mm)	1470
	Ground clearance(mm)	358
Hydraulic system	System working pressure (Mpa)	20
	Boom lifting time (s)	7.2
	Total time (s)	12.9
	Fuel tank capacity (L)	94
Brake system	Service brake	Air-assist hydraulic brake, disc brake
	Parking brake	Manual disc brake
Tyre	Type specification	16/70-20
	Front tyre pressure (kPa)	350
	Rear tyre pressure (kPa)	350